



layout top view

free space required for battery replacement if holder not mounted on edge of P.C. board

Contact materials:  
 Battery contacts : Ni 99,6  
 Solder pins: tin-plated 100% Sn

- Samples can deviate in the execution from the serie.

- Dimensions and tolerances can be specified only after the testing of the devices for the mass production definitely

All framed values will be used for dimension checking !

|           |   |  |  |      |   |  |  |                                |                     |          |           |     |
|-----------|---|--|--|------|---|--|--|--------------------------------|---------------------|----------|-----------|-----|
| Rev.      | ○ |  |  | Rev. | ○ |  |  |                                | Customer's Approval |          |           |     |
| Rev.      | ○ |  |  | Rev. | ○ |  |  |                                | Date                |          |           |     |
| Rev.      | ○ |  |  | Rev. | ○ |  |  |                                | Signature           |          |           |     |
| Titel:    |   |  |  |      |   |  |  | Scale                          | Drawn               | 24.01.05 | SRi       |     |
| NL5077-LF |   |  |  |      |   |  |  |                                | 2:1                 | Checked  | 06.04.05  | MHo |
|           |   |  |  |      |   |  |  |                                | Approved            |          |           |     |
|           |   |  |  |      |   |  |  | CH-4452 Itingen<br>Switzerland |                     |          | 3.8756.4- |     |